

Since 1988

techway®

More is a waste. Less is unthinkable!

2020 Catalogue



LI-ION CORDLESS POWER TOOLS

For Automobile and Construction

techway®

INDEX

CORDLESS POWER TOOLS

CORDLESS POWER TOOLS

IMPACT WRENCH	10
IMPACT DRIVER	18
RATCHET	22
DRILL/DRIVER/SCREWDRIVER	26
POLISHER/SANDER/GRINDER	34
FASTENING TOOLS	38
CAULKING TOOLS/SEALING TOOLS	40
GREASE TOOLS	44
SPECIAL TOOLS	46

AC SERIES TOOLS

AC SERIES TOOLS	52
-----------------------	----

LI-ION BATTERIES/CHARGERS

LI-ION BATTERY PACK (3.6V MINI SERIES)	55
BATTERY & CHARGER SET	55
LI-ION BATTERY PACK (10.8V MINI SERIES)	56
LI-ION BATTERY PACK (14.4V-18.0V MINI SERIES)	57
LI-ION BATTERY PACK (14.4V-18.0V T7 SERIES)	58
LI-ION BATTERY PACK (10.8V-18.0V T8 SERIES)	59
LI-ION BATTERY PACK (18.0V T9 SERIES)	60
LI-ION BATTERY PACK (36.0V T8 SERIES)	61
LI-ION BATTERY PACK (36.0V T9 SERIES)	61

ICON

- **Brushless Motor**
- **4 Pole Motor**
- **Auto Shut-Off Function**
- **TORQUE CONTROL**
- **Replaceable Carbon Brush Motor**
- **Super Power**

INTEGRITY
DILIGENCE
INNOVATION
PROFESSIONALISM



A LEADING MANUFACTURER

techway® Industrial Corporation, founded in 1988, is a leading manufacturer of power tools serving the global professional industry. All products conform to international standards such as UL, CSA, PSE, CE, GS and SAA, and are manufactured to ISO 9001 standards. In order to reduce damage to the environment and conform to the regulations of EC directives, all tools are designed and manufactured in strict compliance to ROHS and WEEE regulations.

Techway Industrial Corporation prides itself on developing and manufacturing the most advanced products in the world. Techway R&D team includes mechanical engineers, electrical engineers, industrial designers, and technicians. The R&D Team is 1/3 of all employees. Techway believes that fast response to market demands, ongoing investment in R&D and improvement in process efficiencies are critical to the sustainability of our competitive edge as a leading manufacturer in the 21st century.



Evolution of High Quality And Endurance

More innovations in 2020!

Impact tools: Higher torque, smaller size, more brushless options.

Ratchet: Higher speed, various ratchet heads (ex: extended head, sealed head).

Grease tool: 10000 psi and 2-speed setting.

Grinder: Super powerful and brushless option.

Riveter: Super powerful and fast brushless option.

Inflator: Easy to use.

**2020
SUPER STAR
NEW PRODUCTS**



Brushless motor

Brushless motors offer several advantages over brushed DC motors listed as below :

- Higher torque
- Higher efficiency
- Higher reliability
- Noise reduction
- Longer lifetime
- Elimination of ionizing sparks
- Reduction of EMI (Electromagnetic Interference)

MINI SERIES

10.8V



B30413815

1500 mAh

B30413825

2500 mAh

B30413820

2000 mAh

B30413830

3000 mAh

MINI SERIES

14.4V



B30414815

1500 mAh

B30414825

2500 mAh

B30414820

2000 mAh

B30414830

3000 mAh

CHARGERS							
SEPARATE CORD				PERMANENT CORD			
C1033038	C1034358	C1081358	C1141358	C1121358	C1039038	C1039358	C1211038
							

CHARGERS					
SEPARATE CORD			PERMANENT CORD		
C1034358	C1141358	C1081358	C1121358	C1039358	C1211038
					

HIGH POWER T7 SERIES 18.0V



B30825820	B30925830	B30925850
2000 mAh	3000 mAh	5000 mAh
B30825825	B30925840	B30925860
2500 mAh	4000 mAh	6000 mAh
B30825830		
3000 mAh		

CHARGERS

SEPARATE CORD

C1036358 C1081358 C1141358 C1121358 C1181358



PERMANENT CORD

HIGH POWER T9 SERIES 18.0V



B31715820	B31615830	B31615850
2000 mAh	3000 mAh	5000 mAh
B31715825	B31615840	B31615860
2500 mAh	4000 mAh	6000 mAh
B31715830		
3000 mAh		

CHARGERS

SEPARATE CORD

C1037358 C1161358 C1171358 C1201358 C1191358 C1241058



techway[®]

CORDLESS POWER TOOLS

IMPACT WRENCH



1/4" · 3/8" CORDLESS IMPACT WRENCH

M26805438 / IWVE1082C

M26805538 / IWVE1083C



MODEL NO	M26805438 / IWVE1082C	M26805538 / IWVE1083C
VOLTAGE	10.8V	10.8V
NO-LOAD SPEED	0~2200 r.p.m.	0~2200 r.p.m.
TORQUE CONTROL	3 TORQUE SECTIONS	3 TORQUE SECTIONS
TORQUE RANGE	FORWARD 1 st	230 kg-cm/23 N-m/17 ft-lb
	FORWARD 2 nd	750 kg-cm/74 N-m/54 ft-lb
	FORWARD 3 rd	1500 kg-cm/147 N-m/108 ft-lb
CAPACITY	1/4" (6.35 mm)	3/8" (10 mm)
IMPACTS PER MINUTE	0~3100	0~3100
MOTOR	Brushless motor	Brushless motor
SIZE (Battery included)	L149 x W54 x H200 mm	L149 x W54 x H200 mm
WEIGHT (Battery included)	0.9 kg	0.9 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS STUBBY IMPACT WRENCH

M26811148 / IWTD1443V



MODEL NO	M26811148 / IWTD1443V
VOLTAGE	14.4V
NO-LOAD SPEED	0~2500 r.p.m.
MAX. TORQUE	3700 kg-cm/362 N-m/266 ft-lb
MAX. TORQUE (Electronic)	269 N-m/199 ft-lb
CAPACITY	3/8" (10 mm)
IMPACTS PER MINUTE	0~3300
MOTOR	Brushless motor
SIZE (Battery included)	L138 x W62 x H233.3 mm
WEIGHT (Battery included)	1.27 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" CORDLESS STUBBY IMPACT WRENCH

M26811248 / IWTD1444V



MODEL NO	M26811248 / IWTD1444V
VOLTAGE	14.4V
NO-LOAD SPEED	0~2500 r.p.m.
MAX. TORQUE	4200 kg-cm/411 N-m/303 ft-lb
MAX. TORQUE (Electronic)	269 N-m/199 ft-lb
CAPACITY	1/2" (13 mm)
IMPACTS PER MINUTE	0~3300
MOTOR	Brushless motor
SIZE (Battery included)	L138 x W62 x H233.3 mm
WEIGHT (Battery included)	1.27 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" · 3/8" CORDLESS IMPACT WRENCH

M26803138 / IWVB1082V

M26803238 / IWVB1083V



MODEL NO	M26803138 / IWVB1082V	M26803238 / IWVB1083V	M26806138 / IWZA1082V	M26806238 / IWZA1083V
VOLTAGE	10.8V	10.8V	10.8V	10.8V
NO-LOAD SPEED	0~2400 r.p.m.	0~2400 r.p.m.	0~2400 r.p.m.	0~2400 r.p.m.
MAX. TORQUE	900 kg-cm/88 N-m/65 ft-lb	1050 kg-cm/103 N-m/76 ft-lb	1080 kg-cm/105 N-m/77 ft-lb	1200 kg-cm/117 N-m/86 ft-lb
CAPACITY	1/4" (6.35 mm)	3/8" (10 mm)	1/4" (6.35 mm)	3/8" (10 mm)
IMPACTS PER MINUTE	0~3200	0~3200	0~3400	0~3400
MOTOR	2 pole	2 pole	2 pole	2 pole
SIZE (Battery included)	L160 x W54 x H192 mm	L160 x W54 x H192 mm	L158 x W54 x H194 mm	L158 x W54 x H194 mm
WEIGHT (Battery included)	1.00 kg	1.00 kg	0.93 kg	0.94 kg

Please check p.55 to p.61 for batteries and chargers.



1/4" · 3/8" CORDLESS IMPACT WRENCH

M26806148 / IWZA1442V

M26806248 / IWZA1443V

1/4" · 3/8" CORDLESS IMPACT WRENCH

M26807148 / IWZB1442V

M26807248 / IWZB1443V



MODEL NO	M26806148 / IWZA1442V	M26806248 / IWZA1443V	M26807148 / IWZB1442V	M26807248 / IWZB1443V
VOLTAGE	14.4V	14.4V	14.4V	14.4V
NO-LOAD SPEED	0~2400 r.p.m.	0~2400 r.p.m.	0~2300 r.p.m.	0~2300 r.p.m.
MAX. TORQUE	1200 kg-cm/117 N-m/86 ft-lb	1400 kg-cm/137 N-m/101 ft-lb	1430 kg-cm/140 N-m/103 ft-lb	1530 kg-cm/150 N-m/110 ft-lb
CAPACITY	1/4" (6.35 mm)	3/8" (10 mm)	1/4" (6.35 mm)	3/8" (10 mm)
IMPACTS PER MINUTE	0~3400	0~3400	0~3400	0~3400
MOTOR	2 pole	2 pole	4 pole	4 pole
SIZE (Battery included)	L158 x W63 x H214 mm	L158 x W63 x H214 mm	L155 x W63 x H214 mm	L155 x W63 x H214 mm
WEIGHT (Battery included)	1.05 kg	1.06 kg	1.08 kg	1.08 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" · 1/2" CORDLESS IMPACT WRENCH

T96805158 / IWXI1803C

T96805258 / IWXI1804C

1/2" CORDLESS IMPACT WRENCH

T96806158 / IWYC1804C



MODEL NO	T96805158 / IWXI1803C	T96805258 / IWXI1804C	T96806158 / IWYC1804C	
VOLTAGE	18.0V	18.0V	18.0V	
NO-LOAD SPEED	0~2300 r.p.m.	0~2400 r.p.m.	0~2100 r.p.m.	
TORQUE CONTROL	4 Torque sections	4 Torque sections	3 Torque sections	
TORQUE RANGE	FORWARD 1 st	663 kg-cm/65 N-m/48 ft-lb	357 kg-cm/35 N-m/26 ft-lb	1020 kg-cm/100 N-m/74 ft-lb
	FORWARD 2 nd	1530 kg-cm/150 N-m/110 ft-lb	1020 kg-cm/100 N-m/74 ft-lb	4000 kg-cm/390 N-m/290 ft-lb
	FORWARD 3 rd	2346 kg-cm/230 N-m/169 ft-lb	1550 kg-cm/152 N-m/113 ft-lb	7500 kg-cm/735 N-m/540 ft-lb
	FORWARD 4 th	5000 kg-cm/490 N-m/360 ft-lb	5500 kg-cm/539 N-m/396 ft-lb	
CAPACITY	3/8" (10 mm)	1/2" (13 mm)	1/2" (13 mm)	
IMPACTS PER MINUTE	0~3100	0~3200	0~2400	
MOTOR	Brushless motor	Brushless motor	Brushless motor	
SIZE (Battery included)	L170 x W78 x H257 mm	L170 x W78 x H257 mm	L180 x W77 x H257 mm	
WEIGHT (Battery included)	2.22 kg	2.22 kg	2.22 kg	

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS IMPACT WRENCH

M26808148 / IWTA1443V

1/4" · 3/8" CORDLESS IMPACT WRENCH

M26803148 / IWVB1442V

M26803248 / IWVB1443V



MODEL NO	M26808148 / IWTA1443V	M26803148 / IWVB1442V	M26803248 / IWVB1443V
VOLTAGE	14.4V	14.4V	14.4V
NO-LOAD SPEED	0~2300 r.p.m.	0~2600 r.p.m.	0~2600 r.p.m.
MAX. TORQUE	4000 kg-cm/392 N-m/288 ft-lb	1200 kg-cm/117 N-m/86 ft-lb	1400 kg-cm/137 N-m/101 ft-lb
CAPACITY	3/8" (10 mm)	1/4" (6.35 mm)	3/8" (10 mm)
IMPACTS PER MINUTE	0~3100	0~3200	0~3200
MOTOR	Brushless motor	2 pole	2 pole
SIZE (Battery included)	L150 x W62 x H229 mm	L160 x W63 x H212 mm	L160 x W63 x H212 mm
WEIGHT (Battery included)	1.32 kg	1.09 kg	1.10 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" · 3/4 " CORDLESS IMPACT WRENCH

T96803158 / IWOE1804V

T96803258 / IWOE1806V



MODEL NO	T96803158 / IWOE1804V	T96803258 / IWOE1806V
VOLTAGE	18.0V	18.0V
NO-LOAD SPEED	0~1500 r.p.m.	0~1500 r.p.m.
MAX. TORQUE	10200 kg-cm/1000 N-m/738 ft-lb	11300 kg-cm/1100 N-m/815 ft-lb
CAPACITY	1/2" (13 mm)	3/4" (19 mm)
IMPACTS PER MINUTE	0~1950	0~1950
MOTOR	Brushless motor	Brushless motor
SIZE (Battery included)	L228.7 x W79 x H294 mm	L237 x W79 x H294 mm
WEIGHT (Battery included)	3.80 kg	3.82 kg

Please check p.55 to p.61 for batteries and chargers.

T9 SERIES

HIGH POWER

T9 SERIES

HIGH POWER

3/8" · 1/2" CORDLESS IMPACT WRENCH

T96801358 / IWHJ1803C

T96801458 / IWHJ1804C

1/2" CORDLESS IMPACT WRENCH

T96802158 / IWN1804C

T9 SERIES

HIGH POWER

18.0V

TBL

MOTOR

TC

3 torque sections



T9 SERIES

HIGH POWER

18.0V

TBL

MOTOR

TC

2 torque sections



MODEL NO	T96801358 / IWHJ1803C	T96801458 / IWHJ1804C	T96802158 / IWN1804C
VOLTAGE	18.0V	18.0V	18.0V
NO-LOAD SPEED	0~2100 r.p.m.	0~2100 r.p.m.	0~1650 r.p.m.
TORQUE CONTROL	3 Torque sections	3 Torque sections	2 torque sections
TORQUE RANGE	FORWARD 1 st	110 kg-cm/10.7 N-m/7.8 ft-lb	130 kg-cm/12.7 N-m/9.3 ft-lb
	FORWARD 2 nd	1000 kg-cm/98 N-m/71.5 ft-lb	1200 kg-cm/117.6 N-m/85.8 ft-lb
	FORWARD 3 rd	3700 kg-cm/362 N-m/266 ft-lb	3900 kg-cm/382 N-m/280 ft-lb
CAPACITY	3/8" (10 mm)	1/2" (13 mm)	1/2" (13 mm)
IMPACTS PER MINUTE	0~3100	0~3100	0~2100
MOTOR	Brushless motor	Brushless motor	2 pole
SIZE (Battery included)	L150 x W76 x H233 mm	L150 x W76 x H233 mm	L267 x W80 x H271.5 mm
WEIGHT (Battery included)	1.69 kg	1.69 kg	3.12 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" · 3/4 " CORDLESS IMPACT WRENCH

T76819158 / IWOD1804V

T76819258 / IWOD1806V

1/2" CORDLESS IMPACT WRENCH

T76806158 / IWJF1804V

T76812158 / IWNC1804V

T7 SERIES

HIGH POWER

18.0V

TBL

MOTOR

NEW



T7 SERIES

HIGH POWER

18.0V

TBL

MOTOR



MODEL NO	T76819158 / IWOD1804V	T76819258 / IWOD1806V	T76806158 / IWJF1804V	T76812158 / IWNC1804V
VOLTAGE	18.0V	18.0V	18.0V	18.0V
NO-LOAD SPEED	0~1500 r.p.m.	0~1500 r.p.m.	0~1650 r.p.m.	0~1650 r.p.m.
MAX. TORQUE	10200 kg-cm/1000 N-m/738 ft-lb	11300 kg-cm/1100 N-m/815 ft-lb	6000 kg-cm/588 N-m/430 ft-lb	6000 kg-cm/590 N-m/435 ft-lb
CAPACITY	1/2" (13 mm)	3/4" (19 mm)	1/2" (13 mm)	1/2" (13 mm)
IMPACTS PER MINUTE	0~1950	0~1950	0~2100	0~2100
MOTOR	Brushless motor	Brushless motor	2 pole	2 pole
SIZE (Battery included)	L228.7 x W79 x H295.5 mm	L237 x W79 x H295.5 mm	L266 x W80 x H265 mm	L267 x W80 x H271 mm
WEIGHT (Battery included)	3.73 kg	3.74 kg	3.09 kg	3.10 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" · 1/2" CORDLESS IMPACT WRENCH

T96801158 / IWHJ1803V

T96801258 / IWHJ1804V

T9 SERIES

HIGH POWER

18.0V

TBL

MOTOR



MODEL NO	T96801158 / IWHJ1803V	T96801258 / IWHJ1804V
VOLTAGE	18.0V	18.0V
NO-LOAD SPEED	0~2100 r.p.m.	0~2100 r.p.m.
MAX. TORQUE	3700 kg-cm/362 N-m/266 ft-lb	3900 kg-cm/382 N-m/280 ft-lb
CAPACITY	3/8" (10 mm)	1/2" (13 mm)
IMPACTS PER MINUTE	0~3100	0~3100
MOTOR	Brushless motor	Brushless motor
SIZE (Battery included)	L150 x W76 x H233 mm	L150 x W76 x H233 mm
WEIGHT (Battery included)	1.69 kg	1.69 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" · 3/4" CORDLESS IMPACT WRENCH

T76811158 / IWOA1804V

T76811358 / IWOA1806V

3/8" · 1/2" CORDLESS IMPACT WRENCH

T76813258 / IWQB1803V

T76813158 / IWQB1804V

T7 SERIES

HIGH POWER

18.0V

4POLE

MOTOR



T7 SERIES

HIGH POWER

18.0V

4POLE

MOTOR



MODEL NO	T76811158 / IWOA1804V	T76811358 / IWOA1806V	T76813258 / IWQB1803V	T76813158 / IWQB1804V
VOLTAGE	18.0V	18.0V	18.0V	18.0V
NO-LOAD SPEED	0~1650 r.p.m.	0~1650 r.p.m.	0~2300 r.p.m.	0~2300 r.p.m.
MAX. TORQUE	8980 kg-cm/880 N-m/650 ft-lb	10200 kg-cm/1000 N-m/378 ft-lb	3650 kg-cm/358 N-m/263 ft-lb	3800 kg-cm/372 N-m/274 ft-lb
CAPACITY	1/2" (13 mm)	3/4" (19 mm)	3/8" (10 mm)	1/2" (13 mm)
IMPACTS PER MINUTE	0~2100	0~2100	0~3000	0~3000
MOTOR	4 pole	4 pole	4 pole	4 pole
SIZE (Battery included)	L233 x W87.5 x H290 mm	L233 x W87.5 x H290 mm	L174 x W80 x H262 mm	L174 x W80 x H262 mm
WEIGHT (Battery included)	3.58 kg	3.59 kg	2.08 kg	2.08 kg

Please check p.55 to p.61 for batteries and chargers.

IMPACT DRIVER



More is a waste. Less is unthinkable
Never Easier

1/4" CORDLESS IMPACT DRIVER

M26605238 / IDVE1080C

MINI SERIES
10.8V



NEW



1/4" CORDLESS IMPACT DRIVER

M26603138 / IDZA1080V

M26602238 / IDVB1080V

MINI SERIES
10.8V



MODEL NO	M26605238 / IDVE1080C
VOLTAGE	10.8V
NO-LOAD SPEED	0~2200 r.p.m.
TORQUE CONTROL	3 TORQUE SECTIONS
TORQUE RANGE	FORWARD 1 st 230 kg-cm/23 N-m/17 ft-lb
	FORWARD 2 nd 750 kg-cm/74 N-m/54 ft-lb
	FORWARD 3 rd 1500 kg-cm/147 N-m/108 ft-lb
CAPACITY	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3100
MOTOR	Brushless motor
SIZE (Battery included)	L149 x W54 x H200 mm
WEIGHT (Battery included)	0.90 kg

Please check p.55 to p.61 for batteries and chargers.

MODEL NO	M26603138 / IDZA1080V	M26602238 / IDVB1080V
VOLTAGE	10.8V	10.8V
NO-LOAD SPEED	0~2400 r.p.m.	0~2400 r.p.m.
MAX. TORQUE	1080 kg-cm/105 N-m/77 ft-lb	900 kg-cm/88 N-m/65 ft-lb
CAPACITY	1/4" (6.35 mm)	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3400	0~3200
MOTOR	2 pole	2 pole
SIZE (Battery included)	L155 x W54 x H194 mm	L157 x W54 x H192 mm
WEIGHT (Battery included)	0.94 kg	0.96 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS STUBBY IMPACT DRIVER

M26608148 / IDTD1440V

MINI SERIES
14.4V



MODEL NO	M26608148 / IDTD1440V
VOLTAGE	14.4V
NO-LOAD SPEED	0~2500 r.p.m.
MAX. TORQUE	2100 kg-cm/205 N-m/152 ft-lb
CAPACITY	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3300
MOTOR	Brushless motor
SIZE (Battery included)	L138 x W62 x H233.3 mm
WEIGHT (Battery included)	1.27 kg

Please check p.55 to p.61 for batteries and chargers.



NEW

1/4" CORDLESS IMPACT DRIVER

M26604148 / IDTA1440V



MODEL NO	M26604148 / IDTA1440V
VOLTAGE	14.4V
NO-LOAD SPEED	0~2300 r.p.m.
MAX. TORQUE	1850 kg-cm/181 N-m/133 ft-lb
CAPACITY	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3100
MOTOR	Brushless motor
SIZE (Battery included)	L147 x W62 x H229 mm
WEIGHT (Battery included)	1.32 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS IMPACT DRIVER

M26604258 / IDTB1800V



MODEL NO	M26604258 / IDTB1800V
VOLTAGE	18.0V
NO-LOAD SPEED	0~3000 r.p.m.
MAX. TORQUE	1850 kg-cm/181 N-m/133 ft-lb
CAPACITY	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3200
MOTOR	Brushless motor
SIZE (Battery included)	L147 x W62 x H229 mm
WEIGHT (Battery included)	1.46 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS IMPACT DRIVER

T96601258 / IDHJ1800C



MODEL NO	T96601258 / IDHJ1800C	
VOLTAGE	18.0V	
NO-LOAD SPEED	0~2100 r.p.m.	
TORQUE CONTROL	3 TORQUE SECTIONS	
TORQUE RANGE	FORWARD 1 st	110 kg-cm/10.7 N-m/7.8 ft-lb
	FORWARD 2 nd	1000 kg-cm/98 N-m/71.5 ft-lb
	FORWARD 3 rd	3700 kg-cm/362 N-m/266 ft-lb
CAPACITY	1/4" (6.35 mm)	
IMPACTS PER MINUTE	0~3100	
MOTOR	Brushless motor	
SIZE (Battery included)	L146 x W76 x H233 mm	
WEIGHT (Battery included)	1.69 kg	

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS IMPACT DRIVER

T96601158 / IDHJ1800V



MODEL NO	T96601158 / IDHJ1800V
VOLTAGE	18.0V
NO-LOAD SPEED	0~2100 r.p.m.
MAX. TORQUE	3700 kg-cm/362 N-m/266 ft-lb
CAPACITY	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3100
MOTOR	Brushless motor
SIZE (Battery included)	L146 x W76 x H233 mm
WEIGHT (Battery included)	1.69 kg

Please check p.55 to p.61 for batteries and chargers.

T9 SERIES
HIGH POWER

1/4" CORDLESS IMPACT DRIVER

M26603148 / IDZA1440V

M26603248 / IDZB1440V



MODEL NO	M26603148 / IDZA1440V	M26603248 / IDZB1440V	M26602248 / IDVB1440V
VOLTAGE	14.4V	14.4V	14.4V
NO-LOAD SPEED	0~2400 r.p.m.	0~2300 r.p.m.	0~2600 r.p.m.
MAX. TORQUE	1200 kg-cm/117 N-m/86.8 ft-lb	1430 kg-cm/140 N-m/103 ft-lb	1200 kg-cm/117 N-m/86 ft-lb
CAPACITY	1/4" (6.35 mm)	1/4" (6.35 mm)	1/4" (6.35 mm)
IMPACTS PER MINUTE	0~3400	0~3400	0~3200
MOTOR	2 pole	4 pole	2 pole
SIZE (Battery included)	L155 x W63 x H214 mm	L155 x W63 x H214 mm	L160 x W63 x H212 mm
WEIGHT (Battery included)	1.07 kg	1.09 kg	1.10 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS IMPACT DRIVER

M26602248 / IDVB1440V



RATCHET

More is a waste. Less is unthinkable
Never Easier

1/4" · 3/8" CORDLESS RATCHET

M25905138 / RWHA1082V M25905238 / RWHA1083V

MINI SERIES
10.8V



1/4" CORDLESS RATCHET

M25906138 / RWHB1082V

MINI SERIES
10.8V



MODEL NO	M25905138 / RWHA1082V	M25905238 / RWHA1083V	M25906138 / RWHB1082V
VOLTAGE	10.8V	10.8V	10.8V
NO-LOAD SPEED	0~220 r.p.m.	0~220 r.p.m.	0~220 r.p.m.
MAX. TORQUE	350 kg-cm/34.3 N-m/25 ft-lb	500 kg-cm/49 N-m/36 ft-lb	581 kg-cm/57 N-m/42 ft-lb
CAPACITY	1/4" (6.35 mm)	3/8" (10 mm)	1/4" (6.35 mm)
MOTOR	2 pole	2 pole	4 pole
SIZE (Battery included)	L289 x W54 x H60 mm	L289 x W54 x H60 mm	L296 x W54 x H65 mm
WEIGHT (Battery included)	0.92 kg	0.97 kg	0.97 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS RATCHET (HIGH SPEED)

M25914138 / RWHE1082V

MINI SERIES
10.8V



3/8" CORDLESS RATCHET (HIGH SPEED)

M25918138 / RWHF1083V

MINI SERIES
10.8V



MODEL NO	M25914138 / RWHE1082V
VOLTAGE	10.8V
NO-LOAD SPEED	0~300 r.p.m.
MAX. TORQUE	470 kg-cm/46 N-m/34 ft-lb
CAPACITY	1/4" (6.35 mm)
MOTOR	4 pole
SIZE (Battery included)	L295 x W54 x H65 mm
WEIGHT (Battery included)	0.98 kg

Please check p.55 to p.61 for batteries and chargers.

MODEL NO	M25918138 / RWHF1083V
VOLTAGE	10.8V
NO-LOAD SPEED	0~220 r.p.m.
MAX. TORQUE	746 kg-cm/73 N-m/54 ft-lb
CAPACITY	3/8" (10 mm)
MOTOR	2 pole
SIZE (Battery included)	L328 x W54 x H65 mm
WEIGHT (Battery included)	1.40 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" CORDLESS RATCHET

M25907238 / RWHC1084V

MINI SERIES
10.8V



MODEL NO	M25907238 / RWHC1084V
VOLTAGE	10.8V
NO-LOAD SPEED	0~170 r.p.m.
MAX. TORQUE	700 kg-cm/68.6 N-m/50.4 ft-lb
CAPACITY	1/2" (10 mm)
MOTOR	2 pole
SIZE (Battery included)	L328 x W54 x H65 mm
WEIGHT (Battery included)	1.35 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS RATCHET

M25906248 / RWHB1443V

MINI SERIES
14.4V



MODEL NO	M25906248 / RWHB1443V
VOLTAGE	14.4V
NO-LOAD SPEED	0~220 r.p.m.
MAX. TORQUE	691 kg-cm/68 N-m/50 ft-lb
CAPACITY	3/8" (10 mm)
MOTOR	4 pole
SIZE (Battery included)	L315 x W62 x H87 mm
WEIGHT (Battery included)	1.10 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS RATCHET (HIGH SPEED)

M25914348 / RWHH1443V

MINI SERIES
14.4V



NEW

MODEL NO	M25914348 / RWHH1443V
VOLTAGE	14.4V
NO-LOAD SPEED	0~300 r.p.m.
MAX. TORQUE	663 kg-cm/65 N-m/48 ft-lb
CAPACITY	3/8" (10 mm)
MOTOR	4 pole
SIZE (Battery included)	L419 x W62 x H87 mm
WEIGHT (Battery included)	1.52 kg

Please check p.55 to p.61 for batteries and chargers.



3/8" · 1/2" CORDLESS RATCHET

M25910148 / RWHD1443V

M25910248 / RWHD1444V

MINI SERIES
14.4V



MODEL NO	M25910148 / RWHD1443V	M25910248 / RWHD1444V
VOLTAGE	14.4V	14.4V
NO-LOAD SPEED	0~180 r.p.m.	0~180 r.p.m.
MAX. TORQUE	1020 kg-cm/100 N-m/73.8 ft-lb	1020 kg-cm/100 N-m/73.8 ft-lb
CAPACITY	3/8" (10 mm)	1/2" (13 mm)
MOTOR	4 pole	4 pole
SIZE (Battery included)	L348 x W87 x H62 mm	L348 x W87 x H62 mm
WEIGHT (Battery included)	1.52 kg	1.52 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS RATCHET (HIGH SPEED)

M25918148 / RWHF1443V

MINI SERIES
14.4V



NEW

MODEL NO	M25918148 / RWHF1443V	M25914148 / RWHE1442V	M25914248 / RWHG1442V
VOLTAGE	14.4V	14.4V	14.4V
NO-LOAD SPEED	0~230 r.p.m.	0~300 r.p.m.	0~300 r.p.m.
MAX. TORQUE	1009 kg-cm/98.9 N-m/73 ft-lb	571 kg-cm/56 N-m/42 ft-lb	553 kg-cm/54 N-m/40 ft-lb
CAPACITY	3/8" (10 mm)	1/4" (6.35 mm)	1/4" (6.35 mm)
MOTOR	4 pole	4 pole	4 pole
SIZE (Battery included)	L348 x W62 x H87 mm	L315 x W62 x H87 mm	L309 x W62 x H87 mm
WEIGHT (Battery included)	1.52 kg	1.10 kg	1.11 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS RATCHET (HIGH SPEED)

M25914148 / RWHE1442V

M25914248 / RWHG1442V

MINI SERIES
14.4V



NEW

DRILL/DRIVER SCREWDRIVER



More is a waste. Less is unthinkable
Never Easier

CORDLESS TWO SPEED DRILL/DRIVER

M26702238 / SDEB1080V

MINI SERIES
10.8V



MODEL NO	M26702238 / SDEB1080V
VOLTAGE	10.8V
NO-LOAD SPEED	L: 0~360 r.p.m. H: 0~1550 r.p.m.
MAX. TORQUE	245 kg-cm/24 N-m/17.6 ft-lb
CHUCK CAPACITY	3/8" (1.0~10 mm)
CLUTCH	2 pole
MOTOR	10 sections + 1 drill
SIZE (Battery included)	L199 x W54 x H193 mm
WEIGHT (Battery included)	1.04 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS TWO SPEED DRILL/DRIVER

M26703138 / SDFB1080V

MINI SERIES
10.8V



MODEL NO	M26702238 / SDEB1080V
VOLTAGE	10.8V
NO-LOAD SPEED	L: 0~360 r.p.m. H: 0~1550 r.p.m.
MAX. TORQUE	240 kg-cm/23.5 N-m/17ft-lb
CHUCK CAPACITY	3/8" (1.5~10 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L199 x W54 x H216 mm
WEIGHT (Battery included)	1.04 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS TWO SPEED DRILL/DRIVER

M26702248 / SDEB1440V

MINI SERIES
14.4V



MODEL NO	M26702248 / SDEB1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~340 r.p.m. H: 0~1400 r.p.m.
MAX. TORQUE	265 kg-cm/26 N-m/19.2 ft-lb
CHUCK CAPACITY	3/8" (0.8~10 mm)
CLUTCH	2 pole
MOTOR	10 sections + 1 drill
SIZE (Battery included)	L199 x W63 x H215 mm
WEIGHT (Battery included)	1.16 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS TWO SPEED DRILL/DRIVER

M26702448 / SDEH1440V

MINI SERIES
14.4V



MODEL NO	M26702448 / SDEH1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~330 r.p.m. H: 0~1350 r.p.m.
MAX. TORQUE	275 kg-cm/27 N-m/20ft-lb
CHUCK CAPACITY	3/8" (0.8~10 mm)
CLUTCH	10 sections + 1 drill
MOTOR	4 pole
SIZE (Battery included)	L199 x W63 x H215 mm
WEIGHT (Battery included)	1.16 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS TWO SPEED DRILL/DRIVER

M26703148 / SDFB1440V



MODEL NO	M26703148 / SDFB1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~340 r.p.m. H: 0~1400 r.p.m.
MAX. TORQUE	265 kg-cm/26 N-m/19 ft-lb
CHUCK CAPACITY	3/8" (1.5~10 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L199 x W63 x H216 mm
WEIGHT (Battery included)	2.15 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS TWO SPEED DRILL/DRIVER

M26703248 / SDFD1440V



MODEL NO	M26703248 / SDFD1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~330 r.p.m. H: 0~1350 r.p.m.
MAX. TORQUE	275 kg-cm/27 N-m/20ft-lb
CHUCK CAPACITY	3/8" (1.5~10 mm)
CLUTCH	10 sections + 1 drill
MOTOR	4 pole
SIZE (Battery included)	L199 x W63 x H216 mm
WEIGHT (Battery included)	1.16 kg


Please check p.55 to p.61 for batteries and chargers.

1/2" CORDLESS TWO SPEED DRILL/DRIVER

T76702348 / DEFC1440V

T76702358 / DEFC1800V

T76703158 / DEIA1800V



- Variable speed drill/driver.
- Aluminum clutch ring.
- Ergonomic soft grip handle for comfortable use.
- Gear box with spindle lock function and single sleeve chuck.

MODEL NO	T76702348 / DEFC1440V	T76702358 / DEFC1800V	T76703158 / DEIA1800V
VOLTAGE	14.4V	18.0V	18.0V
NO-LOAD SPEED	L: 0~325 r.p.m. H: 0~1170 r.p.m.	L: 0~340 r.p.m. H: 0~1220 r.p.m.	L: 0~460 r.p.m. H: 0~1600 r.p.m.
MAX. TORQUE	400 kg-cm/39.2 N-m/29 ft-lb	460 kg-cm/45.1 N-m/33 ft-lb	612 kg-cm/60 N-m/44.3 ft-lb
CHUCK CAPACITY	3/8" (1.5~10 mm)	1/2" (1.5~13 mm)	1/2" (13 mm)
CLUTCH	17 sections + 1 drill	16 sections + 1 drill	15 sections + 1 drill
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L212 x W80 x H250 mm	L226 x W80 x H254 mm	L245 x W206 x H262 mm
WEIGHT (Battery included)	1.82 kg	2.00 kg	2.34 kg

Please check p.55 to p.61 for batteries and chargers.

1/2" CORDLESS TWO SPEED DRILL/DRIVER

T96701158 / DEJC1800V



MODEL NO	T96701158 / DEJC1800V
VOLTAGE	18.0V
NO-LOAD SPEED	L: 0~370 r.p.m. H: 0~1570 r.p.m.
MAX. TORQUE	326 kg-cm/32 N-m/23.6 ft-lb
CHUCK CAPACITY	1/2" (13 mm)
CLUTCH	10 sections + 1 drill
MOTOR	Brushless motor
SIZE (Battery included)	L184 x W76 x H235 mm
WEIGHT (Battery included)	1.67 kg

Please check p.55 to p.61 for batteries and chargers.





1/2" CORDLESS TWO SPEED DRILL/DRIVER (HAMMER)

T76502348 / DHFC1440V

T76502358 / DHFC1800V

T76503158 / DHIA1800V



- Variable speed drill/driver.
- Aluminum clutch ring.
- Ergonomic soft grip handle for comfortable use.
- Gear box with spindle lock function and single sleeve chuck.

MODEL NO	T76502348 / DHFC1440V	T76502358 / DHFC1800V	T76503158 / DHIA1800V
VOLTAGE	14.4V	18.0V	18.0V
NO-LOAD SPEED	L: 0~325 r.p.m. H: 0~1170 r.p.m.	L: 0~340 r.p.m. H: 0~1220 r.p.m.	L: 0~460 r.p.m. H: 0~1600 r.p.m.
MAX. TORQUE	400 kg-cm/39.2 N-m/29 ft-lb	460 kg-cm/45.1 N-m/33 ft-lb	612 kg-cm/60 N-m/44.3 ft-lb
CHUCK CAPACITY	3/8" (1.5~10 mm)	1/2" (1.5~13 mm)	1/2" (13 mm)
IMPACTS PER MINUTE	L: 3900 H: 14040	L: 4560 H: 16560	L: 5520 H: 19200
CLUTCH	17 sections + 1 drill + hammer	17 sections + 1 drill + hammer	
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L227 x W80 x H250 mm	L241 x W80 x H254 mm	L253 x W80 x H262 mm
WEIGHT (Battery included)	0.92 kg	2.31 kg	2.63 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26303118 / SFC A0360S

M26303218 / SFC B0360S



MODEL NO	M26303118 / SFC A0360S	M26303218 / SFC B0360S
VOLTAGE	3.6V	3.6V
NO-LOAD SPEED	L: 220 r.p.m. H: 450 r.p.m.	L: 220 r.p.m. H: 450 r.p.m.
MAX. TORQUE	40 kg-cm/3.9 N-m/2.9 ft-lb	40 kg-cm/3.9 N-m/2.9 ft-lb
CAPACITY	1/4" (6.35 mm)	1/4" (6.35 mm)
CLUTCH	15 sections + 1 drill	15 sections + 1 drill
MOTOR	2 pole	2 pole
SIZE (Battery included)	L268 x W43 x H48 mm	L283 x W43 x H48 mm
WEIGHT (Battery included)	0.51 kg	0.53 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26304248 / SDE A1440V



MODEL NO	M26304248 / SDE A1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~340 r.p.m. H: 0~1400 r.p.m.
MAX. TORQUE	265 kg-cm/26 N-m/19.2 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L140 x W63 x H215 mm
WEIGHT (Battery included)	1.00 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26304448 / SDE G1440V



MODEL NO	M26304448 / SDE G1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~330 r.p.m. H: 0~1350 r.p.m.
MAX. TORQUE	275 kg-cm/27 N-m/20 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	4 pole
SIZE (Battery included)	L140 x W63 x H215 mm
WEIGHT (Battery included)	1.00 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26304238 / SDE A1080V



MODEL NO	M26304238 / SDE A1080V
VOLTAGE	10.8V
NO-LOAD SPEED	L: 0~360 r.p.m. H: 0~1550 r.p.m.
MAX. TORQUE	245 kg-cm/24 N-m/17.6 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L140 x W54 x H193 mm
WEIGHT (Battery included)	0.83 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26305138 / SDFA1080V



MODEL NO	M26305138 / SDFA1080V
VOLTAGE	10.8V
NO-LOAD SPEED	L: 0~360 r.p.m. H: 0~1550 r.p.m.
MAX. TORQUE	240 kg-cm/23.5 N-m/17 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L158 x W54 x H216 mm
WEIGHT (Battery included)	0.88 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26305148 / SDFA1440V



MODEL NO	M26305148 / SDFA1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~340 r.p.m. H: 0~1400 r.p.m.
MAX. TORQUE	265 kg-cm/26 N-m/19 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	2 pole
SIZE (Battery included)	L158 x W63 x H215 mm
WEIGHT (Battery included)	1.00 kg

Please check p.55 to p.61 for batteries and chargers.

1/4" CORDLESS TWO SPEED SCREWDRIVER

M26305248 / SDFC1440V



MODEL NO	M26305248 / SDFC1440V
VOLTAGE	14.4V
NO-LOAD SPEED	L: 0~330 r.p.m. H: 0~1350 r.p.m.
MAX. TORQUE	275 kg-cm/27 N-m/20 ft-lb
CHUCK CAPACITY	1/4" (6.35 mm)
CLUTCH	10 sections + 1 drill
MOTOR	4 pole
SIZE (Battery included)	L158 x W63 x H216 mm
WEIGHT (Battery included)	1.00 kg

Please check p.55 to p.61 for batteries and chargers.

techway® DRILL/DRIVER/SCREWDRIVER

More is a waste. Less is unthinkable
Never Easier

CORDLESS DRYWALL SCREWDRIVER

T75305148 / DWAB1440V T75305158 / DWAB1800V T75306148 / DWBB1440V T75306158 / DWBB1800V

T7 SERIES HIGH POWER
14.4V

T7 SERIES HIGH POWER
18.0V

- Adjustable depth locator assembly for consistent screw depth.
- Powerful motor to handle all drywall applications.
- Aluminum gear housing to enhance durability.
- Ergonomic soft grip handle for comfortable use.



MODEL NO	T75305148 / DWAB1440V	T75305158 / DWAB1800V	T75306148 / DWBB1440V	T75306158 / DWBB1800V
VOLTAGE	14.4V	18.0V	14.4V	18.0V
NO-LOAD SPEED	0~1900 r.p.m.	0~1600 r.p.m.	0~4500 r.p.m.	0~4000 r.p.m.
MAX. TORQUE	102 kg-cm/10 N-m/7.4 ft-lb	112 kg-cm/11 N-m/8.1 ft-lb	82 kg-cm/8 N-m/5.9 ft-lb	92 kg-cm/9 N-m/6.6 ft-lb
FASTENER RANGE	16~55 mm length	16~55 mm length	16~55 mm length	16~55 mm length
BIT SPEC	1/4"×75L + ⊕# 2×25L mm	1/4"×75L + ⊕# 2×25L mm	1/4"×75L + ⊕# 2×25L mm	1/4"×75L + ⊕# 2×25L mm
MOTOR	2 pole	2 pole	2 pole	2 pole
SIZE (Battery included)	L235 x W80 x H254 mm	L235 x W80 x H254 mm	L235 x W80 x H254 mm	L235 x W80 x H254 mm
WEIGHT(Battery included)	1.74 kg	1.87 kg	1.74 kg	1.87 kg


Please check p.55 to p.61 for batteries and chargers.

CORDLESS AUTOFEED SCREWDRIVER

16-25 mm Length T75311148 / ASLB1440V T75311158 / ASLB1800V
T75312148 / ASMB1440V T75312158 / ASMB1800V
25-55 mm Length T75310148 / ASJB1440V T75310158 / ASJB1800V
T75309148 / ASIB1440V T75309158 / ASIB1800V

T7 SERIES HIGH POWER
14.4V

T7 SERIES HIGH POWER
18.0V



- 20000 R.P.M high-torque motor.
- Screw using range: 16-25 mm / 25-55 mm
- Reverse switch.
- Feeds screws continuously or individually.



MODEL NO	T75311148 / ASLB1440V	T75311158 / ASLB1800V	T75312148 / ASMB1440V	T75312158 / ASMB1800V
VOLTAGE	14.4V	18.0V	14.4V	18.0V
NO-LOAD SPEED	0~1900 r.p.m.	0~1600 r.p.m.	0~4500 r.p.m.	0~4000 r.p.m.
MAX. TORQUE	102 kg-cm/10 N-m/7.4 ft-lb	112 kg-cm/11 N-m/8.1 ft-lb	82 kg-cm/8 N-m/5.9 ft-lb	92 kg-cm/9 N-m/6.6 ft-lb
FASTENER RANGE	16-25 mm length	16-25 mm length	16-25 mm length	16-25 mm length
BIT SPEC	1/4" × 143 L	1/4" × 143 L	1/4" × 143 L	1/4" × 143 L
MOTOR	2 pole	2 pole	2 pole	2 pole
SIZE (Battery included)	L340 x W80 x H254 mm	L340 x W80 x H254 mm	L340 x W80 x H254 mm	L340 x W80 x H254 mm
WEIGHT(Battery included)	2.25 kg	2.38 kg	2.25 kg	2.36 kg


MODEL NO	T75310148 / ASJB1440V	T75310158 / ASJB1800V	T75309148 / ASIB1440V	T75309158 / ASIB1800V
VOLTAGE	14.4V	18.0V	14.4V	18.0V
NO-LOAD SPEED	0~4500 r.p.m.	0~4000 r.p.m.	0~1900 r.p.m.	0~1600 r.p.m.
MAX. TORQUE	82 kg-cm/8 N-m/5.9 ft-lb	92 kg-cm/9 N-m/6.6 ft-lb	102 kg-cm/10 N-m/7.4 ft-lb	112 kg-cm/11 N-m/8.1 ft-lb
FASTENER RANGE	25-55 mm length	25-55 mm length	25-55 mm length	25-55 mm length
BIT SPEC	1/4" × 173 L	1/4" × 173 L	1/4" × 173 L	1/4" × 173 L
MOTOR	2 pole	2 pole	2 pole	2 pole
SIZE (Battery included)	L396 x W80 x H254 mm	L396 x W80 x H254 mm	L396 x W80 x H254 mm	L396 x W80 x H254 mm
WEIGHT(Battery included)	2.26 kg	2.39 kg	2.28 kg	2.41 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS AUTOFEED SCREWDRIVER

16-25 mm Length T75314158 / ASOA1800V
25-55 mm Length T75313158 / ASNA1800V

T7 SERIES HIGH POWER
18.0V



- 20000 R.P.M high-torque motor.
- Screw using range: 16-25 mm / 25-55 mm
- Reverse switch.
- Feeds screws continuously or individually.

MODEL NO	T75314158 / ASOA1800V	T75313158 / ASNA1800V
VOLTAGE	18.0V	18.0V
NO-LOAD SPEED	L: 0~1800 r.p.m. H: 0~5000 r.p.m.	L: 0~1800 r.p.m. H: 0~5000 r.p.m.
MAX. TORQUE	L: 142 kg-cm/14 N-m/10.3 ft-lb H: 102 kg-cm/10 N-m/7.4 ft-lb	L: 142 kg-cm/14 N-m/10.3 ft-lb H: 102 kg-cm/10 N-m/7.4 ft-lb
FASTENER RANGE	16-25 mm length	25-55 mm length
BIT SPEC	1/4" × 173 L	1/4" × 173 L
MOTOR	2 pole	2 pole
SIZE (Battery included)	L350 x W80 x H262 mm	L407 x W80 x H262 mm
WEIGHT(Battery included)	2.49 kg	2.54 kg

Please check p.55 to p.61 for batteries and chargers.

Accessories

A1530130A / 1ADJA007

A1530130A = A1530110A + A1530120A

MODEL NO	A1530130A / 1ADJA007
SIZE	L700 x W150 x H71 mm
WEIGHT	0.97 kg

EXTENSION BAR A1530110A



CARRY BAG A1530120A



CORDLESS POWER TOOLS

POLISHER

SANDER

GRINDER

More is a waste. Less is unthinkable
Never Easier

CORDLESS PALM POLISHER

M25702138 / POCA1080S | M25702148 / POCA1440S | M25702248 / POCA1440V

MINI SERIES
10.8V



MINI SERIES
14.4V



Variable Speed



MODEL NO	M25702138 / POCA1080S	M25702148 / POCA1440S	M25702248 / POCA1440V
VOLTAGE	10.8V	14.4V	14.4V
NO-LOAD SPEED	3500 r.p.m.	3400 r.p.m.	1500~3400 r.p.m.
ORBIT	4.7 mm	4.7 mm	4.7 mm
PAD THREAD (Male)	5/16" - 24 UNF	5/16" - 24 UNF	5/16" - 24 UNF
PAD SIZE	5"	5"	5", 6"
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L190 x W125 x H145 mm	L204 x W123 x H146 mm	L204 x W123 x H146 mm
WEIGHT (Battery included)	1.3 kg	1.45 kg	1.45 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS POLISHER / SANDER

M25701138 / MSAA1080S | M25701338 / MSAC1080S

MINI SERIES
10.8V



MINI SERIES
14.4V



MODEL NO	M25701138 / MSAA1080S	M25701338 / MSAC1080S
VOLTAGE	10.8V	10.8V
NO-LOAD SPEED	3000 r.p.m.	7500 r.p.m.
PAD THREAD	(Male) 5/16" - 24 UNF	(Female) 1/4" - 20 UNF
MOTOR	2 pole	2 pole
SIZE (Battery included)	L140 x W54 x H178 mm	L140 x W54 x H178 mm
WEIGHT (Battery included)	0.88 kg	0.88 kg

Please check p.55 to p.61 for batteries and chargers.

MODEL NO	M25705148 / MSAF1440V
VOLTAGE	14.4V
NO LOAD SPEED (Sander)	0~6900 r.p.m.
NO LOAD SPEED (Polisher)	0~1900 r.p.m.
PAD THREAD (Male)	5/16" - 24 UNF
PAD SIZE (Sander)	2"
PAD SIZE (Polisher)	3"
MOTOR	4 pole
SIZE (Battery included)	L150 x W55 x H219 mm
WEIGHT (Battery included)	0.88 kg

Please check p.55 to p.61 for batteries and chargers.

techway®

POLISHER/SANDER/GRINDER

CORDLESS POWER POLISHER

T75701558 / POBF1800V T75701158 / POBC1800V



MODEL NO	T75701558 / POBF1800V	T75701158 / POBC1800V
VOLTAGE	18.0V	18.0V
NO-LOAD SPEED	500 r.p.m.	1300~3800 r.p.m.
ORBIT	NO	4.7 mm
PAD THREAD	(Female / Male) 5/16" - 24 UNF	(Male) 5/16" - 24 UNF
PAD SIZE	5"	5"
MOTOR	2 pole	2 pole
SIZE (Battery included)	L376 x W240 x H153 mm	L376 x W240 x H153 mm
WEIGHT (Battery included)	2.30 kg	2.30 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS ANGLE DIE GRINDER

M25101138 / MGAA1080S



MODEL NO	M25101138 / MGAA1080S
VOLTAGE	10.8V
NO-LOAD SPEED	22000 r.p.m.
COLLET CAPACITY	φ3
OPTIONAL	φ6, 1/8", 1/4"
MOTOR	2 pole
SIZE (Battery included)	L147 x W54 x H178 mm
WEIGHT (Battery included)	0.80 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS ANGLE GRINDER (HEAVY DUTY)

T95102158 / GDOB1800S



MODEL NO	T95102158 / GDOB1800S
VOLTAGE	18.0V
NO-LOAD SPEED	6500 r.p.m.
WHEEL SIZE	4" (105 mm) / 4-1/2" (115 mm) / 5" (125 mm)
THREAD	M10x1.5 / M14x2 / 5"/8-11 UNC
MOTOR	Brushless motor
SIZE (Battery included, w/o handle)	L362 x W142 x H123 mm
SIZE (Battery and handle included)	L362 x W242 x H123 mm
WEIGHT (Battery included)	2.26 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS ANGLE GRINDER

T95101158 / GDNC1800S



MODEL NO	T95101158 / GDNC1800S
VOLTAGE	18.0V
NO-LOAD SPEED	7500 r.p.m.
WHEEL SIZE	4" (105 mm) / 4-1/2" (115 mm) / 5" (125 mm)
THREAD	M10x1.5 / M14x2 / 5"/8-11 UNC
MOTOR	Brushless motor
SIZE (Battery included, w/o handle)	L360 x W132 x H123 mm
SIZE (Battery and handle included)	L360 x W220 x H123 mm
WEIGHT (Battery included)	2.16 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS DIE GRINDER

M25103138 / MGBA1080S M25102238 / MGBB1080S M25102248 / MGBB1440V M25103148 / MGBA1440S M25103148 / MGBA1440S



MODEL NO	M25103138 MGBA1080S	M25102238 MGBB1080S	M25102248 MGBB1440V	M25103148 MGBA1440S	M25105148 MGCB1440V
VOLTAGE	10.8V	10.8V	14.4V	14.4V	14.4V
NO-LOAD SPEED	21000 r.p.m.	3600 r.p.m.	0~3800 r.p.m.	21000 r.p.m.	0~3400 r.p.m.
COLLET CAPACITY	φ6	φ6	φ6	φ6	φ6
OPTIONAL	φ3, 1/4", 1/8"	φ3, 1/4", 1/8"	φ3, 1/8", 1/4"	φ3, 1/8", 1/4"	φ3, 1/8", 1/4"
CAPACITY	1/4" (6.35 mm)	1/4" (6.35 mm)			
MOTOR	2 pole	4 pole	4 pole	4 pole	4 pole
SIZE (Battery included)	L260 x W80 x H55 mm	L268 x W80 x H55 mm	L290 x W100 x H62 mm	L285 x W100 x H62 mm	L303 x W100 x H63 mm
WEIGHT (Battery included)	0.78 kg	0.90 kg	1.05 kg	0.90 kg	1.22 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS ANGLE GRINDER

T75101258 / GDNA1800S



MODEL NO	T75101258 / GDNA1800S
VOLTAGE	18.0V
NO-LOAD SPEED	7000 r.p.m.
WHEEL SIZE	4" (105 mm) / 4-1/2" (115 mm) / 5" (125 mm)
THREAD	M10x1.5 / M14x2 / 5"/8-11 UNC
MOTOR	Brushless motor
SIZE (Battery included, w/o handle)	L360 x W132 x H123 mm
SIZE (Battery and handle included)	L360 x W220 x H123 mm
WEIGHT (Battery included)	2.33 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS ANGLE GRINDER

T75103158 / GDKC1800S



MODEL NO	T75103158 / GDKC1800S
VOLTAGE	18.0V
NO-LOAD SPEED	7000 r.p.m.
WHEEL SIZE	4" (105 mm) / 4-1/2" (115 mm) / 5" (125 mm)
THREAD	M10x1.5 / M14x2 / 5"/8-11 UNC
MOTOR	4 pole
SIZE (Battery included, w/o handle)	L360 x W132 x H123 mm
SIZE (Battery and handle included)	L360 x W220 x H123 mm
WEIGHT (Battery included)	2.33 kg

Please check p.55 to p.61 for batteries and chargers.

FASTENING TOOLS



More is a waste. Less is unthinkable
Never Easier

CORDLESS PRECISION FASTENING TOOL

T96901158 / TSAE1800S T96901258 / TSAE1801S T96901358 / TSAE1802S T96901458 / TSAE1803S

T9 SERIES
18.0V

BL
MOTOR



NEW



MODEL NO	T96901158 / TSAE1800S	T96901258 / TSAE1801S	T96901358 / TSAE1802S	T96901458 / TSAE1803S
VOLTAGE	18.0V	18.0V	18.0V	18.0V
NO-LOAD SPEED	700 r.p.m.	700 r.p.m.	1160 r.p.m.	1160 r.p.m.
TORQUE RANGE	50~122 kg-cm/5~12 N-m /3.69~8.85 ft-lb	30.6~81.6 kg-cm/3~8 N-m /2.21~5.9 ft-lb	10.2~40.8 kg-cm/1~4 N-m /0.74~2.95 ft-lb	5.1~20.4 kg-cm/0.5~2 N-m /0.37~1.48 ft-lb
CAPACITY (Hex driver)	1/4" (6.35 mm)	1/4" (6.35 mm)	1/4" (6.35 mm)	1/4" (6.35 mm)
MOTOR	Brushless motor	Brushless motor	Brushless motor	Brushless motor
SIZE (Battery included)	L209 x W76 x H249 mm	L209 x W76 x H249 mm	L209 x W76 x H249 mm	L209 x W76 x H249 mm
WEIGHT (Battery included)	1.72 kg	1.72 kg	1.72 kg	1.72 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLES PRECISION SCREW DRIVER

T96902158 / TSCA1800S

T9 SERIES
18.0V

BL
MOTOR



NEW



MODEL NO	T96902158 / TSCA1800S
VOLTAGE	18.0V
NO-LOAD SPEED	800 r.p.m.
TORQUE RANGE	24.47~122.36 kg-cm/2.4~12 N-m/1.77~8.85 ft-lb
CAPACITY	1/4" (6.35 mm)
MOTOR	Brushless motor
SIZE (Battery included)	L200 x W76 x H235 mm
WEIGHT (Battery included)	1.70 kg

Please check p.55 to p.61 for batteries and chargers.

3/8" CORDLESS PRECISION ANGLE WRENCH

T96902158 / TSBB1800S

T9 SERIES
18.0V

BL
MOTOR



NEW



MODEL NO	T96902158 / TSBB1800S
VOLTAGE	18.0V
NO-LOAD SPEED	300 r.p.m.
TORQUE RANGE	153~306 kg-cm/15~30 N-m/11~22 ft-lb
CAPACITY	3/8" (10 mm)
MOTOR	Brushless motor
SIZE (Battery included)	L506 x W116 x H76 mm
WEIGHT (Battery included)	2.42 kg

Please check p.55 to p.61 for batteries and chargers.

T9 SERIES
HIGH POWER

CAULKING TOOLS SEALING TOOLS



More is a waste. Less is unthinkable
Never Easier

CORDLESS CAULKING TOOL & SEALING TOOL

T65806118 / CSBA0363V T65806218 / CSBA0364V T65806318 / CSBA0366V

MINI SERIES
3.6V

- Applicable to both sausage bag and cartridge.
Three options for capacity: 310/400/600 ml.
- Patented dripless mechanism.
- Patented rapid plunger release mechanism.
- Speed control function.
- The switch shuts off the tool when plunger reaches the end.



For both cartridge and sausage bag applications.



MODEL NO	T65806118 / CSBA0363V	T65806218 / CSBA0364V	T65806318 / CSBA0366V
VOLTAGE	3.6V	3.6V	3.6V
CAPACITY	310 ml	400 ml	600 ml
MAX. EXPEL FORCE	300 kgf/2490 N/660 lb	300 kgf/2490 N/660 lb	300 kgf/2490 N/660 lb
NO-LOAD SPEED	3~8 mm/sec	3~8 mm/sec	3~8 mm/sec
PERFORMANCE	"22 tubes of 9" silicone for a fully charged battery at room temperature		
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L405 x W141 x H254 mm	L450 x W141 x H254 mm	L550 x W141 x H254 mm
WEIGHT (Battery included)	1.80 kg	1.88 kg	2.02 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS CAULKING TOOL & SEALING TOOL

T65805138 / CSBA1083V T65805238 / CSBA1084V T65805338 / CSBA1086V

MINI SERIES
10.8V

- Applicable to both sausage bag and cartridge.
Three options for capacity: 310/400/600 ml.
- Patented dripless mechanism.
- Patented rapid plunger release mechanism.
- Speed control function.
- The switch shuts off the tool when plunger reaches the end.



For both cartridge and sausage bag applications.



MODEL NO	T65805138 / CSBA1083V	T65805238 / CSBA1084V	T65805338 / CSBA1086V
VOLTAGE	10.8V	10.8V	10.8V
CAPACITY	310 ml	400 ml	600 ml
MAX. EXPEL FORCE	450 kgf/4410 N/990 lb	450 kgf/4410 N/990 lb	450 kgf/4410 N/990 lb
NO-LOAD SPEED	3~10 mm/sec	3~10 mm/sec	3~10 mm/sec
PERFORMANCE	"123 tubes of 9" silicone for a fully charged battery at room temperature		
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L420 x W141 x H282 mm	L460 x W141 x H282 mm	L560 x W141 x H282 mm
WEIGHT (Battery included)	2.13 kg	2.20 kg	2.35 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS CAULKING TOOL & SEALING TOOL

M25806138 / CSFA1083V M25806238 / CSFA1084V M25806338 / CSFA1086V

MINI SERIES

10.8V

- Applicable to both sausage bag and cartridge.
- Three options for capacity: 310/400/600 ml.
- Patented dripless mechanism.
- Patented rapid plunger release mechanism.
- Speed control function.
- The switch shuts off the tool when plunger reaches the end.

For both cartridge and sausage bag applications.

Variable speed trigger

Speed dial control

MODEL NO	M25806138 / CSFA1083V	M25806238 / CSFA1084V	M25806338 / CSFA1086V
VOLTAGE	10.8V	10.8V	10.8V
CAPACITY	310 ml	400 ml	600 ml
MAX. EXPEL FORCE	600 kgf/5880 N/1320 lb	600 kgf/5880 N/1320 lb	600 kgf/5880 N/1320 lb
NO-LOAD SPEED	1.8~9 mm/sec	1.8~9 mm/sec	1.8~9 mm/sec
PERFORMANCE	"75 tubes of 9"(sika221) silicone for a fully charged battery at room temperature		
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L420 x W145 x H280 mm	L460 x W145 x H280 mm	L560 x W145 x H280 mm
WEIGHT (Battery included)	2.39 kg	2.47 kg	2.62 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS SEALING TOOL

T75805148 / CSFA1443V T75805248 / CSFA1444V T75805348 / CSFA1446V

T7 SERIES

HIGH POWER

14.4V

- Applicable to both sausage bag and cartridge.
- Three options for capacity: 310/400/600 ml.
- Patented dripless mechanism.
- Patented rapid plunger release mechanism.
- Speed control function.
- The switch shuts off the tool when plunger reaches the end.

For both cartridge and sausage bag applications.

MODEL NO	T75805148 / CSFA1443V	T75805248 / CSFA1444V	T75805348 / CSFA1446V
VOLTAGE	14.4V	14.4V	14.4V
CAPACITY	310 ml	400 ml	600 ml
MAX. EXPEL FORCE	650 kgf/6370 N/1430 lb	650 kgf/6370 N/1430 lb	650 kgf/6370 N/1430 lb
NO-LOAD SPEED	0~10 mm/sec	0~10 mm/sec	0~10 mm/sec
PERFORMANCE	"237 tubes of 9" silicone for a fully charged battery at room temperature		
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L420 x W136 x H289 mm	L460 x W136 x H289 mm	L560 x W136 x H289 mm
WEIGHT (Battery included)	2.82 kg	2.90 kg	3.05 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS EPOXY TOOL

T75801148 / EGAC1443V T75801158 / EGAC1803V

T7 SERIES

HIGH POWER

14.4V

T7 SERIES

HIGH POWER

18.0V

- Expels up to 90 tubes of 380ml epoxy with one fully charged battery.
- The switch shuts off the tool when plunger reaches the end.
- Variable speed dial to control the flow.
- Soft grip for comfortable use.

MODEL NO	T75801148 / EGAC1443V	T75801158 / EGAC1803V
VOLTAGE	14.4V	18.0V
CAPACITY	380 ml	380 ml
MAX. EXPEL FORCE	550 kgf/5390 N/1210 lb	700 kgf/6860 N/1540 lb
NO-LOAD SPEED	1.5~4.5 mm/sec	1.5~5 mm/sec
PERFORMANCE	90 tubes of 380 ml cartridge for a fully charged battery at room temperature	94 tubes of 380 ml cartridge for a fully charged battery at room temperature
MOTOR	2 pole	2 pole
SIZE (Battery included)	L387 x W140 x H238 mm	L387 x W140 x H238 mm
WEIGHT (Battery included)	2.98 kg	3.12 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS SEALING TOOL

T75805458 / CSFA1803V T75805558 / CSFA1804V T75805658 / CSFA1806V

T7 SERIES

HIGH POWER

18.0V

- Applicable to both sausage bag and cartridge.
- Three options for capacity: 310/400/600 ml.
- Patented dripless mechanism.
- Patented rapid plunger release mechanism.
- Speed control function.
- The switch shuts off the tool when plunger reaches the end.

For both cartridge and sausage bag applications.

MODEL NO	T75805458 / CSFA1803V	T75805558 / CSFA1804V	T75805658 / CSFA1806V
VOLTAGE	18.0V	18.0V	18.0V
CAPACITY	310 ml	400 ml	600 ml
MAX. EXPEL FORCE	650 kgf/6370 N/1430 lb	650 kgf/6370 N/1430 lb	650 kgf/6370 N/1430 lb
NO-LOAD SPEED	1.5~10 mm/sec	1.5~10 mm/sec	1.5~10 mm/sec
PERFORMANCE	"231 tubes of 9"(sika221) silicone for a fully charged battery at room temperature		
MOTOR	2 pole	2 pole	2 pole
SIZE (Battery included)	L420 x W145 x H289 mm	L460 x W145 x H289 mm	L560 x W145 x H289 mm
WEIGHT (Battery included)	2.93 kg	3.01 kg	3.16 kg

Please check p.55 to p.61 for batteries and chargers.

GREASE TOOLS

CORDLESS GREASE TOOL

T95501158 / GRHB1800V

T9 SERIES HIGH POWER
18.0V

MODEL NO	T95501158 / GRHB1800V
VOLTAGE	18.0V
DELIVERY (/min)	High speed 290+/-30 g/min Low speed 125+/-10 g/min
MAX. PRESSURE	10000 psi
ACCEPTABLE GREASE	>NLGI #2
MOTOR	2 pole
SIZE (Battery included)	L400 x W90 x H227 mm
WEIGHT (Battery included)	4.70 kg

Please check p.55 to p.61 for batteries and chargers.



NEW

T9 SERIES HIGH POWER

CORDLESS GREASE TOOL

M25501148 / GRDD1440S M25501158 / GRDD1800S

MINI SERIES
14.4V

MINI SERIES
18.0V



CORDLESS GREASE TOOL

T75501148 / GRDA1440S T75501158 / GRDA1800S

T7 SERIES HIGH POWER
14.4V

T7 SERIES HIGH POWER
18.0V



Pressure Safety Valve

- This valve is set to 6000 psi, 6250 psi by different voltage.
- When the tools is blocked during grease output, the over-pressure protection would shut off the tool.

MODEL NO	M25501148 / GRDD1440S	M25501158 / GRDD1800S	T75501148 / GRDA1440S	T75501158 / GRDA1800S
VOLTAGE	14.4V	18.0V	14.4V	18.0V
DELIVERY (/min)	70 g/min	75 g/min	75 g/min	75 g/min
MAX. PRESSURE	6000 psi	6250 psi	6000 psi	6250 psi
ACCEPTABLE GREASE	>NLGI #2	>NLGI #2	>NLGI #2	>NLGI #2
MOTOR	2 pole	2 pole	2 pole	2 pole
SIZE (Battery included)	L121 x W79 x H487 mm	L121 x W79 x H487 mm	L196 x W80 x H487 mm	L196 x W80 x H487 mm
WEIGHT (Battery included)	3.40 kg	3.44 kg	3.65 kg	3.88 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS SHEAR WRENCH

T975011A8 / SWAB3600S

T9 SERIES HIGH POWER
36.0V



MODEL NO	T975011A8 / SWAB3600S
VOLTAGE	36.0V
NO-LOAD SPEED	15 r.p.m.
MAX. TORQUE	10200 kg-cm/1000 N-m/738 ft-lb
AVAILABLE DIRECTION	0°, 90°, 180°, 270°
SUITABLE KINDS OF TC BOLT	M16, M20, M22, M24
QUANTITIES OF M24 TC BOLT	310 pcs
QUANTITIES OF M22 TC BOLT	380 pcs
MOTOR	Brushless motor
SIZE (Battery included)	L266.6 X W108 X H355.3 mm
WEIGHT (Battery included)	7.90 kg

Please check p.55 to p.61 for batteries and chargers.



NEW

T9 SERIES HIGH POWER

CORDLESS BELT SANDER

M25106148 / BSAA1440V

MINI SERIES
14.4V



MODEL NO	M25106148 / BSAA1440V
VOLTAGE	14.4V
NO-LOAD SPEED	6500 r.p.m.
BELT SIZE	1/2" x 18" (long) 3/8" x 13" (short)
MOTOR	4 pole
SIZE (Battery included)	L380 X W135 X H90 mm (long) L335 X W135 X H90 mm (short)
WEIGHT (Battery included)	1.37 kg (long) 1.29 kg (short)

Please check p.55 to p.61 for batteries and chargers.

CORDLESS POWER SHEAR

T75201258 / PSBE1800S

T7 SERIES HIGH POWER
18.0V



- Powerful DC motor provides continual cutting durability.
- Cool ventilation system for motor.
- The model with laser ray indicator is not available for North America.

MODEL NO	T75201258 / PSBE1800S
VOLTAGE	18.0V
NO-LOAD SPEED	4500 r.p.m.
MAX. STEEL THICKNESS	1.6 mm
MAX. CURVE CUTTING	1.2 mm
LASER	No
MOTOR	2 pole
SIZE (Battery included)	L351 x W80 x H158 mm
WEIGHT (Battery included)	2.20 kg

Please check p.55 to p.61 for batteries and chargers.

T9 SERIES

HIGH POWER

CORDLESS RIVETER

T96101158 / CRBB1800S

T9 SERIES

HIGH POWER

18.0V



NEW



- High working efficiency.
- Pull one ϕ 6.4 mm stainless steel rivet in 1.2 seconds.

MODEL NO	T96101158 / CRBB1800S
VOLTAGE	18.0V
STROKE	25 mm
RIVET SIZE	ϕ 2.4, 3.2, 4.0, 4.8 & 5 (6.4 mm)
RIVET MATERIAL	Aluminum, Steel, Stainless Steel
MAX PULLING FORCE	2000 kgf/19600 N/4400 lb
MOTOR	Brushless motor
SIZE (Battery included)	L290 x H298 x W80 mm
WEIGHT (Battery included)	2.43 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS RIVETER

T76102158 / CRBC1800S

T7 SERIES

HIGH POWER

18.0V



NEW



- High working efficiency.
- Pull one ϕ 6.4 mm stainless steel rivet in 1.2 seconds.

MODEL NO	T76102158 / CRBC1800S
VOLTAGE	18.0V
STROKE	25 mm
RIVET SIZE	ϕ 2.4, 3.2, 4.0, 4.8 & 5 (6.4 mm)
RIVET MATERIAL	Aluminum, Steel, Stainless Steel
MAX PULLING FORCE	2000 kgf/19600 N/4400 lb
MOTOR	Brushless motor
SIZE (Battery included)	L290 x H295 x W80 mm
WEIGHT (Battery included)	2.41 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS RECIPROCATING SAW

M27001148 / RSAA1440V

MINI SERIES

14.4V



MODEL NO	M27001148 / RSAA1440V
VOLTAGE	14.4V
NO-LOAD SPEED	0~3000 s.p.m.
STROKE LENGTH	14mm
MOTOR	4 POLE
SIZE (Battery included)	L388 x W88 x H62 mm
WEIGHT (Battery included)	1.39 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS RECIPROCATING SAW

T97001158 / RSBB1800C

T9 SERIES

HIGH POWER

18.0V



NEW



MODEL NO	T97001158 / RSBB1800C
VOLTAGE	18.0V
NO-LOAD SPEED	0~3100 s.p.m.
STROKE LENGTH	32mm
MOTOR	Brushless motor
SIZE (Battery included)	L384 x W78 x H245 mm
WEIGHT (Battery included)	3.42 kg

Please check p.55 to p.61 for batteries and chargers.

T9 SERIES

HIGH POWER



CORDLESS FLASHLIGHT

M25602138 / FLCA1080S M25602148 / FLCA1440S



MODEL NO	M25602138 / FLCA1080S		M25602148 / FLCA1440S		M25602238 / FLFA1080S
VOLTAGE	10.8V		14.4V		10.8V
LED	Ø 5 LED		Ø 5 LED		0.2 W LED
LED BULB	28 pcs LED	4 pcs LED	28 pcs LED	4 pcs LED	4/16 pcs
ILLUMINANCE	160 lux/1 m	35 lux/1 m	160 lux/1 m	35 lux/1 m	100/300 lux/40 m
LED LIFE	3000 hrs		3000 hrs		5000 hrs
RUN-TIME	9 hrs	40 hrs	11 hrs	52 hrs	18 hrs/4.5 hrs
SIZE (Battery included)	L60 x W54 x H297 mm		L87 x W63 x H317 mm		L60 x W54 x H297 mm
WEIGHT (Battery included)	0.45 kg		0.57 kg		0.43 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS FLASHLIGHT

M25602238 / FLFA1080S



MODEL NO	M25602138 / FLCA1080S		M25602148 / FLCA1440S		M25602238 / FLFA1080S
VOLTAGE	10.8V		14.4V		10.8V
LED	Ø 5 LED		Ø 5 LED		0.2 W LED
LED BULB	28 pcs LED	4 pcs LED	28 pcs LED	4 pcs LED	4/16 pcs
ILLUMINANCE	160 lux/1 m	35 lux/1 m	160 lux/1 m	35 lux/1 m	100/300 lux/40 m
LED LIFE	3000 hrs		3000 hrs		5000 hrs
RUN-TIME	9 hrs	40 hrs	11 hrs	52 hrs	18 hrs/4.5 hrs
SIZE (Battery included)	L60 x W54 x H297 mm		L87 x W63 x H317 mm		L60 x W54 x H297 mm
WEIGHT (Battery included)	0.45 kg		0.57 kg		0.43 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS FLASHLIGHT

T75601148 / FLAC1440S T75601158 / FLAD1800S



- Pivoting head rotates 300° horizontally and 150° vertically which allows light to be projected in any direction.
- Super bright 28 LED light panel for great light on virtually any job.
- Works with 14.4 V and 18 V TECHWAY series batteries.

MODEL NO	T75601148 / FLAC1440S	T75601158 / FLAD1800S
VOLTAGE	14.4V	18.0V
LED	Ø5 LED	Ø5 LED
ILLUMINANCE	250 lux/1 m	250 lux/1 m
LED LIFE	3000 hrs	3000 hrs
RUN-TIME	14.5 hrs	16.0 hrs
SIZE (Battery included)	L136 x W89 x H284 mm	L145 x W89 x H284 mm
WEIGHT (Battery included)	1.14 kg	1.15 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS FLASHLIGHT

M25601338 / FLEA1080S M25601348 / FLEA1440S



MODEL NO	M25601338 / FLEA1080S	M25601348 / FLEA1440S	T75603158 / FLEB1800S
VOLTAGE	10.8V	14.4V	10.8V
LED	3W LED	3W LED	3W LED
LUMINOUS FLUX	136 lm	136 lm	136 lm
ILLUMINANCE	5000 lux/1m	5000 lux/1m	
LED LIFE	50000 hrs	50000 hrs	50000 hrs
RUN-TIME	4 hrs	7.5 hrs	6.5 hrs (1.5 Ah)/13.5 hrs (3.0 Ah)
SIZE (Battery included)	L74 x W70 x H263 mm	L88 x W70 x H284 mm	L138 x W80 x H238 mm
WEIGHT (Battery included)	0.5 kg	0.62 kg	1.07 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS FLASHLIGHT

T75603158 / FLEB1800S



- Professional and reliable flashlight for virtually any job.
- Ultra bright light with high power 3W LED bulb.
- Works with 18.0V Techway series batteries.

CORDLESS INFLATOR

M27601138 / IFAA1080S



- Inflator tube (Standard length: 90 cm. Customized lengths are also available.)

NEW

MODEL NO	M27601138 / IFAA1080S	M27601148 / IFAA1440S
VOLTAGE	10.8V	14.4V
MAX PRESSURE	130 psi	150 psi
HOSE LENGTH	15 cm~90 cm (customized)	15 cm~90 cm (customized)
MOTOR	2 POLE	2 POLE
SIZE (Battery included)	L139 x W56 x H228 mm	L139 x W56 x H248 mm
WEIGHT (Battery included)	0.73 kg	0.85 kg

Please check p.55 to p.61 for batteries and chargers.

CORDLESS INFLATOR

M27601148 / IFAA1440S



- Inflator tube (Standard length: 90 cm. Customized lengths are also available.)

NEW

AC SERIES TOOLS



AC SPRAY SET

HVLP1000

AC SERIES
1000W

HIGH VOLUME LOW PRESSURE PAINTING SYSTEM
SUITABLE FOR THE FOLLOWING PAINTS:

- Lacquer / Stain
- Clear coat
- Water borne coatings
- Oil-based paint
- Latex

MODEL NO	HVLP1000
INPUT POWER	1000W
PRESSURE	4 psi
AIR CONSUMPTION	48 CFM
MOTOR	2 pole
SIZE (Spray Tank And Tube)	L507 X W227 X H278 mm
WEIGHT (With Spray Tank And Tube)	5.20 kg



1/2 "AC IMPACT WRENCH

T96819129 / IWEB1104V

T96819149 / IWEB2204V

AC SERIES
650W



FEATURES

- Heavy-duty impacting transmission.
- All metal transmission for extended durability All metal transmission for extended durability
- Ergonomic soft grip handle for comfortable use.
- Powerful motor with replaceable carbon brush.
- Special elastic handle material reduces 50% of vibration.



MODEL NO	T96819129 / IWEB1104V	T96819149 / IWEB2204V
VOLTAGE	110~120V 50/60 Hz	220~240V 50/60 Hz
NO-LOAD SPEED	0~2150 r.p.m.	0~2150 r.p.m.
RATING	650W	650W
CAPACITY	1/2" (13 mm)	1/2" (13 mm)
MAX TORQUE	5500 kg-cm/539 N-m/396 ft-lb	5500 kg-cm/539 N-m/396 ft-lb
MOTOR	Replaceable carbon brush motor	Replaceable carbon brush motor
SIZE	L290 x W81 x H237 mm	L290 x W81 x H237 mm
WEIGHT	3.50 kg	3.50 kg

BATTERY CHARGER

LI-ION BATTERY PACK (Mini Series)

MINI SERIES 3.6V

B30111815
1500 mAh

B30111820
2000 mAh

B30111825
2500 mAh

B30111830
3000 mAh



CHARGING TIME


3.6V	C1011018
B30111815 0.08 kg/1500 mAh	100% 60 min
B30111820 0.08 kg/2000 mAh	100% 70 min
B30111825 0.08 kg/2500 mAh	100% 90 min
B30111830 0.08 kg/3000 mAh	100% 110 min



SEPARATE CORD

C1011018
Input: 100~240 VAC
Output: 3.6V 2A
Size: L145 x W109 x H61 mm
Weight: 0.32 kg

PLUG OPTIONS



BATTERY & CHARGER SET



C1081358
For MINI SERIES 10.8~18.0V
For T7 SERIES 14.4~18.0V
For plug-in and slide type battery
Input: 100~240 VAC
Output: 10.8~18.0V 3.4A
Size: L180 x W121 x H80 mm
Weight: 0.58 kg



C1141358
For MINI SERIES 10.8~18.0V
For T7 SERIES 14.4~18.0V
For plug-in and slide type battery
Input: 100~240 VAC
Output: 10.8~18.0V
5.5A for High Power Series
3.4A for Mini-Tech Series
USB Output: 5V 500mA
Size: L200 x W134 x H86 mm
Weight: 0.89 kg



C1201358
For MINI SERIES 10.8~18.0V
For T8 and T9 SERIES 10.8~18.0V
For slide type battery
Input: 100~240 VAC
Output: 10.8~18.0V 5.5A
USB Output: 5V 500 mA
Size: L200 x W134 x H85 mm
Weight: 0.89 kg

LI-ION BATTERY PACK (Mini Series)

MINI SERIES

10.8V

B30513815

1500 mAh

B30513820

2000 mAh

B30513825

2500 mAh

B30513830

3000 mAh

B30313815

1500 mAh

B30313820

2000 mAh

B30313825

2500 mAh

B30313830

3000 mAh

B30413815

1500 mAh

B30413820

2000 mAh

B30413825

2500 mAh

B30413830

3000 mAh

Fuel gauge

SEPARATE CORD

C1033038

Input: 100~240 VAC

Output: 10.8V 2A

Size: L145 x W109 x H61 mm

Weight: 0.33 kg

C1034358

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H61 mm

Weight: 0.39 kg

C1081358

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A

Size: L180 x W121 x H80 mm

Weight: 0.58 kg

C1141358

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A for High Power Series

3.4A for Mini-Tech Series

USB Output: 5V 500mA

Size: L200 x W134 x H86 mm

Weight: 0.89 kg

PLUG OPTIONS

UL

BS

GS

CCC

PSE

SAA

PERMANENT CORD

C1039038

Input: 100~240 VAC

Output: 10.8V 2A

Size: L145 x W109 x H57 mm

Weight: 0.47 kg

C1039358

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H57 mm

Weight: 0.47 kg

C1211038

Input: 100~240 VAC

Output: 10.8V 1A

Size: L78 x W43 x H52 mm (US Type Adaptor)

L68 x W57 x H50 mm (Charger Stand)

Weight: 0.18 kg

CHARGING TIME					
10.8V	C1033038 C1039038	C1034358 C1039358	C1081358	C1141358	C1211038
B30513815 B30313815 B30413815 0.20 kg/1500 mAh	80% 45 min 100% 60 min	80% 25 min 100% 30 min	80% 25 min 100% 30 min	80% 25 min 100% 30 min	100% 100 min
B30513820 B30313820 B30413820 0.20 kg/2000 mAh	80% 55 min 100% 70 min	80% 35 min 100% 40 min	80% 35 min 100% 40 min	80% 35 min 100% 40 min	100% 135 min
B30513825 B30313825 B30413825 0.20 kg/2500 mAh	80% 75 min 100% 85 min	80% 45 min 100% 55 min	80% 40 min 100% 53 min	80% 40 min 100% 53 min	100% 170 min
B30513830 B30313830 B30413830 0.20 kg/3000 mAh	80% 95 min 100% 105 min	80% 55 min 100% 70 min	80% 48 min 100% 60 min	80% 45 min 100% 65 min	100% 215 min

LI-ION BATTERY PACK (Mini Series)

MINI SERIES

14.4V

B30424815

1500 mAh

B30424820

2000 mAh

B30424825

2500 mAh

B30424830

3000 mAh

B30414815

1500 mAh

B30414820

2000 mAh

B30414825

2500 mAh

B30414830

3000 mAh

B30425815

1500 mAh

B30425820

2000 mAh

B30425825

2500 mAh

B30425830

3000 mAh

B30415815

1500 mAh

B30415820

2000 mAh

B30415825

2500 mAh

B30415830

3000 mAh

Fuel gauge

SEPARATE CORD

C1034358

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H61 mm

Weight: 0.39 kg

C1081358

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A

Size: L180 x W121 x H80 mm

Weight: 0.58 kg

C1141358

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A for High Power Series

3.4A for Mini-Tech Series

USB Output: 5V 500 mA

Size: L200 x W134 x H86 mm

Weight: 0.89 kg

PLUG OPTIONS

UL

BS

GS

CCC

PSE

SAA

PERMANENT CORD

C1039358

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H57 mm

Weight: 0.47 kg

C1221048

Input: 100~240 VAC

Output: 14.4V 1A

Size: L78 x W43 x H52 mm (US Type Adaptor)

L68 x W57 x H50 mm (Charger Stand)

Weight: 0.18 kg

CHARGING TIME				
14.4V	C1034358 C1039358	C1081358	C1141358	C1221048
B30424815 B30414815 0.32 kg/1500 mAh	80% 25 min 100% 30 min	80% 25 min 100% 30 min	80% 25 min 100% 30 min	100% 100 min
B30424820 B30414820 0.32 kg/2000 mAh	80% 35 min 100% 40 min	80% 35 min 100% 40 min	80% 35 min 100% 40 min	100% 135 min
B30424825 B30414825 0.32 kg/2500 mAh	80% 45 min 100% 55 min	80% 40 min 100% 53 min	80% 40 min 100% 53 min	100% 170 min
B30424830 B30414830 0.32 kg/3000 mAh	80% 55 min 100% 70 min	80% 48 min 100% 60 min	80% 45 min 100% 65 min	100% 215 min
18.0V	C1034358 C1039358	C1081358	C1141358	
B30425815 B30415815 0.36 kg/1500 mAh	80% 35 min 100% 40 min	80% 25 min 100% 30 min	80% 25 min 100% 30 min	
B30425820 B30415820 0.36 kg/2000 mAh	80% 45 min 100% 50 min	80% 35 min 100% 40 min	80% 35 min 100% 40 min	
B30425825 B30415825 0.36 kg/2500 mAh	80% 60 min 100% 65 min	80% 40 min 100% 53 min	80% 40 min 100% 53 min	
B30425830 B30415830 0.36 kg/3000 mAh	80% 75 min 100% 80 min	80% 48 min 100% 60 min	80% 45 min 100% 65 min	

56 ■ CORDLESS POWER TOOLS

CORDLESS POWER TOOLS ■ 57

LI-ION BATTERY PACK (T7 Series)

T7 SERIES HIGH POWER 14.4V	B30824820 2000 mAh	B30924830 3000 mAh
	B30824825 2500 mAh	B30924840 4000 mAh
	B30824830 3000 mAh	B30924850 5000 mAh
		B30924860 6000 mAh

T7 SERIES HIGH POWER 18.0V	B30825820 2000 mAh	B30925830 3000 mAh
	B30825825 2500 mAh	B30925840 4000 mAh
	B30825830 3000 mAh	B30925850 5000 mAh
		B30925860 6000 mAh



SEPARATE CORD

C1036358

For slide type battery

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H77 mm

Weight: 0.43 kg

C1081358

For plug-in and slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A

Size: L180 x W121 x H80 mm

Weight: 0.58 kg

C1141358

For plug-in and slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A for High Power Series

3.4A for Mini-Tech Series

USB Output: 5 V 500mA

Size: L200 x W134 x H86 mm

Weight: 0.91 kg

PLUG OPTIONS

UL

BS

GS

CCC

PSE

SAA

PERMANENT CORD

C1181358

For slide type battery

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 x H57 mm

Weight: 0.47 kg

CHARGING TIME				
14.4V	C1036358 C1181358	C1081358	C1141358	
B30824820 0.37 kg/2000 mAh	80% 35 min 100% 40 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	
B30824825 0.37 kg/2500 mAh	80% 45 min 100% 55 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	
B30824830 B30924830 0.55 kg/3000 mAh	80% 55 min 100% 60 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	
B30924840 0.55 kg/4000 mAh	80% 75 min 100% 80 min	80% 65 min 100% 80 min	80% 41 min 100% 53 min	
B30924850 0.55 kg/5000 mAh	80% 95 min 100% 110 min	80% 85 min 100% 100 min	80% 51 min 100% 65 min	
B30924860 0.55 kg/6000 mAh	80% 115 min 100% 140 min	80% 105 min 100% 120 min	80% 61 min 100% 78 min	
18.0V	C1036358 C1181358	C1081358	C1141358	
B30825820 0.43 kg/2000 mAh	80% 45 min 100% 50 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	
B30825825 0.43 kg/2500 mAh	80% 60 min 100% 65 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	
B30825830 B30925830 0.68 kg/3000 mAh	80% 75 min 100% 80 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	
B30925840 0.68 kg/4000 mAh	80% 95 min 100% 100 min	80% 65 min 100% 80 min	80% 41 min 100% 53 min	
B30925850 0.68 kg/5000 mAh	80% 125 min 100% 135 min	80% 85 min 100% 100 min	80% 51 min 100% 65 min	
B30925860 0.68 kg/6000 mAh	80% 155 min 100% 165 min	80% 105 min 100% 120 min	80% 61 min 100% 78 min	

LI-ION BATTERY PACK (T8 Series)

T8 SERIES HIGH POWER 10.8V	B31313820 2000 mAh		T8 SERIES HIGH POWER 14.4V	B31314820 2000 mAh		T8 SERIES HIGH POWER 18.0V	B31315820 2000 mAh	B31415840 4000 mAh
	B31313825 2500 mAh			B31314825 2500 mAh			B31315825 2500 mAh	B31415850 5000 mAh
	B31313830 3000 mAh			B31314830 3000 mAh			B31315830 3000 mAh	B31415860 6000 mAh



SEPARATE CORD

C1037358

For slide type battery

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 X H70 mm

Weight: 0.40 kg

C1161358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A

Size: L180 x W121 x H78 mm

Weight: 0.56 kg

C1171358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A

USB Output: 5V 500mA

Size: L200 x W134 x H87 mm

Weight: 0.89 kg

C1201358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A

USB Output: 5V 500mA

Size: L200 x W134 x H85 mm

Weight: 0.89 kg

PLUG OPTIONS

UL

BS

GS

CCC

PSE

SAA

CHARGING TIME				
10.8V	C1037358 C1191358	C1161358	C1171358 C1201358	
B30824820 0.27 kg/2000 mAh	80% 35 min 100% 40 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	
B30824825 0.27 kg/2500 mAh	80% 45 min 100% 55 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	
B30924830 0.27 kg/3000 mAh	80% 55 min 100% 60 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	
14.4V	C1037358 C1191358	C1161358	C1171358 C1201358	
B31314820 0.35 kg/2000 mAh	80% 35 min 100% 40 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	
B31314825 0.35 kg/2500 mAh	80% 45 min 100% 53 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	
B31314830 0.35 kg/3000 mAh	80% 55 min 100% 60 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	
18.0V	C1037358 C1191358	C1161358	C1171358 C1201358	C1241058
B31315820 0.42 kg/2000 mAh	80% 45 min 100% 50 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	100% 70 min
B31315825 0.42 kg/2500 mAh	80% 60 min 100% 65 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	100% 90 min
B31315830 0.42 kg/3000 mAh	80% 75 min 100% 80 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	100% 110 min
B31415840 0.70 kg/4000 mAh	80% 95 min 100% 100 min	80% 65 min 100% 80 min	80% 41 min 100% 53 min	100% 130 min
B31415850 0.70 kg/5000 mAh	80% 125 min 100% 135 min	80% 85 min 100% 100 min	80% 51 min 100% 65 min	100% 165 min
B31415860 0.70 kg/6000 mAh	80% 155 min 100% 165 min	80% 105 min 100% 120 min	80% 61 min 100% 78 min	100% 205 min

T9 SERIES HIGH POWER

LI-ION BATTERY PACK (T9 Series)

T9 SERIES HIGH POWER

18.0V

B31715820

4000 mAh

B31715825

2500 mAh

B31715830

3000 mAh

T9 SERIES HIGH POWER

18.0V

B31615830

3000 mAh

B31615840

4000 mAh

B31615850

5000 mAh

B31615860

6000 mAh

NEW



Fuel gauge

NEW



Fuel gauge

NEW



NEW



NEW



NEW



PLUG OPTIONS













SEPARATE CORD

C1037358

For slide type battery

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 X H70 mm

Weight: 0.40 kg

C1161358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 3.4A

Size: L180 x W121 x H78 mm

Weight: 0.56 kg

C1171358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A

USB Output: 5V 500 mA

Size: L200 x W134 x H87 mm

Weight: 0.89 kg

C1201358

For slide type battery

Input: 100~240 VAC

Output: 10.8~18.0V 5.5A

USB Output: 5V 500 mA

Size: L200 x W134 x H85 mm

Weight: 0.89 kg

PERMANENT CORD

C1191358

For slide type battery

Input: 100~240 VAC

Output: 10.8~14.4V 3A

18.0V 2.3A

Size: L145 x W109 X H57 mm

Weight: 0.47 kg

C1241058

For slide type battery

Input: 100~240 VAC

Output: 18.0V 2A

Size: L110 x W59 x H65 mm (US Type Adaptor)

L87 x W63 x H31 mm (Charger Stand)

Weight: 0.35 kg

CHARGING TIME				
18.0V	C1037358 C1191358	C1161358	C1171358 C1201358	C1241058
B31715820 0.44 kg/2000 mAh	80% 45 min 100% 50 min	80% 35 min 100% 40 min	80% 19 min 100% 27 min	100% 70 min
B31715825 0.44 kg/2500 mAh	80% 60 min 100% 65 min	80% 40 min 100% 53 min	80% 25 min 100% 37 min	100% 90 min
B31715830 0.44 kg/2500 mAh	80% 75 min 100% 80 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	100% 110 min
B31315830 0.72 kg/3000 mAh	80% 75 min 100% 80 min	80% 45 min 100% 60 min	80% 31 min 100% 43 min	100% 110 min
B31415840 0.72 kg/4000 mAh	80% 95 min 100% 100 min	80% 65 min 100% 80 min	80% 41 min 100% 53 min	100% 130 min
B31415850 0.72 kg/5000 mAh	80% 125 min 100% 135 min	80% 85 min 100% 100 min	80% 51 min 100% 65 min	100% 165 min
B31415860 0.72 kg/6000 mAh	80% 155 min 100% 165 min	80% 105 min 100% 120 min	80% 61 min 100% 78 min	100% 205 min

LI-ION BATTERY PACK (T8 Series)

T8 SERIES HIGH POWER

36.0V

B3141A830

3000 mAh

B3141A840

4000 mAh

B3141A850

5000 mAh

B3141A860

6000 mAh

NEW



NEW



PLUG OPTIONS













SEPARATE CORD

C11515A8

For slide type battery

Input: 100~240 VAC

Output: 36.0V 6A

Size: L219 x W157 x H93 mm

Weight: 1.20 kg

CHARGING TIME

36.0V	C11515A8
B3141A830 1.40 kg/3000 mAh	80% 20 min 100% 35 min
B3141A840 1.40 kg/4000 mAh	80% 35 min 100% 45 min
B3141A850 1.40 kg/5000 mAh	80% 40 min 100% 60 min
B3141A860 1.40 kg/6000 mAh	80% 50 min 100% 70 min

LI-ION BATTERY PACK (T9 Series)

T9 SERIES HIGH POWER

36.0V

B3161A830

3000 mAh

B3161A840

4000 mAh

B3161A850

5000 mAh

B3161A860

6000 mAh

NEW



NEW



Fuel gauge

PLUG OPTIONS













SEPARATE CORD

C11515A8

For slide type battery

Input: 100~240 VAC

Output: 36.0V 6A

Size: L219 x W157 x H93 mm

Weight: 1.20 kg

CHARGING TIME

36.0V	C11515A8
B3161A830 1.40 kg/3000 mAh	80% 20 min 100% 35 min
B3161A840 1.40 kg/4000 mAh	80% 35 min 100% 45 min
B3161A850 1.40 kg/5000 mAh	80% 40 min 100% 60 min
B3161A860 1.40 kg/6000 mAh	80% 50 min 100% 70 min

techway®

More is a waste. Less is unthinkable!



TECHWAY INDUSTRIAL CO., LTD.

朝程工業股份有限公司

地址：台中市40850工業區21路32號

ADDRESS: No.32, Gongyequ 21st Rd. Nantun Dist., Taichung City 40850 Taiwan (R.O.C.)

TEL: 8864-2350-9298 FAX: 8864-2350-9708 / 8864-2350-9708

EMAIL: sales4@techway.com.tw www.techway.com.tw

Printed on January 01, 2020



TECHWAY new catalogue